

5011 INDOOR TEMPORARY COATING

KATS 5011 is an environmentally friendly combination of waterborne chemistry that provides a temporary paint scratch protection during assembly as well as light paint overspray protection in easy water removable, closed film coating.

The surfaces to be protected should be clean and dry.

KATS 5011 can be applied using a water-compatible HVLP or conventional spray system. HVLP is recommended due to its transfer efficiency.

Ambient/Surface Temperature..... 45° - 100°F (7° - 38°C)
 Ideal Surface Temperature 60° - 80°F (16° - 27°C)
 Note: Insure the coating is dry before exposing to the elements.

Wet Film Thickness ... 3 - 5 mil (76.2 - 127.0 microns)
 Dry Film Thickness 0.3 - 0.5 mil (7.62 - 12.70 microns)
 Typical Coverage..... 352 - 587 ft²/gal (8.6 - 14.4 m²/l)

BENEFITS:

- Zero VOC
- Easily removed with water
- No masking
- Low labor time and cost for application and removal
- No plastic film to dispose of
- Can be removed up to 6 months after application
- Nonoffensive odor
- Contains no hazardous air pollutants
- Elimination of costs associated with surface damage

APPLICATIONS:

KATS 5011 can be used for indoor antimutilation purpose as well as masking agent for paint oversprays. Typical applications include:

- Automobiles
- Boats / watercraft
- Recreational vehicles, ATVs
- Machine tools
- Farm equipment
- Trucks
- Construction equipment

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
ASTM D-2196 Modified	Brookfield Viscometer Spindle #1 @ 72°F (22°C) and 12 RPM, cps	100 - 300
ASTM D-1475	Density	8.4 - 8.6 lb/gal (1.01 - 1.03 g/cm ³)

* Based on KATS 5080 test data.

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

A Division of The Whitmore Manufacturing Company

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
 An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • www.katscoatings.com

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.