

## 5200 CHROME PROTECTANT

KATS 5200 is a water based coating modified with sustainable technology designed to protect chrome surface from environmental damage with excellent early water resistance. It may require high pressure water or mild sponge agitation during final rinsing. The coating is easily cleaned off with KATS 8077 or Kwik Kleen Concentrate cleaner.

The surfaces to be protected should be clean and dry. Block unwanted area to prevent overspray. Apply KATS 5200 in an enclosed area without excessive wind. KATS 5200 can be applied using a water-compatible HVLP or conventional spray system. HVLP is recommended due to its transfer efficiency.

Ambient/Surface Temperature..... 45° - 100°F (7° - 38°C)  
 Ideal Surface Temperature ..... 60° - 80°F (16° - 27°C)  
 Note: Insure the coating is dry before exposing to the elements.

Wet Film Thickness ... 3 - 5 mil (76.2 - 127.0 microns)  
 Dry Film Thickness .... 0.3 - 0.5 mil (7.62 - 12.70 microns)  
 Typical Coverage..... 352 - 587 ft<sup>2</sup>/gal (8.6 - 14.4 m<sup>2</sup>/l)

### BENEFITS:

- Trace amount of VOC
- Elimination of costs associated with surface damage
- Modified with sustainable technology
- Low labor time (and cost) for application and cleaning
- No plastic film to dispose of
- Can be removed up to 6 months after application
- No offensive odor
- Contains no hazardous air pollutants
- Biodegradable and environmentally safe

### APPLICATIONS:

KATS 5200 is most often used to protect chrome surface during transit and storage. Typical applications include:

- Automobiles
- Boats / watercraft
- Recreational vehicles, ATVs
- Machine tools
- Farm equipment

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
ASTM D-2196	Brookfield Viscosity Spindle #4 @ 72°F (22°C) and 60 rpm, cps	1000 - 3000
ASTM D-1475	Density	8.4 lb/gal (1.008 g/cm <sup>3</sup> )

*The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

### PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

*A Division of* **The Whitmore Manufacturing Company**

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108  
 An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • [www.katscoatings.com](http://www.katscoatings.com)

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.