

5550

INDOOR RUST PROTECTIVE COATING

KATS 5550 is a water based synthetic polymer coating designed to protect painted or unpainted surfaces from rust and corrosion during temporary indoor storage.

KATS 5550 is a multipurpose product formulated to protect surfaces from high humidity and is removable using the KATS 8077.

Apply KATS 5550 to a clean and dry surface.

KATS 5550 can be applied using a water based compatible HVLP or conventional spray system. HVLP is recommended due to its transfer efficiency. It can also be dipped as well as sprayed through a common pump-up sprayer.

Ambient/Surface Temperature..... 45° - 100°F (7° - 38°C)
 Ideal Surface Temperature 60° - 80°F (16° - 27°C)
 Note: Insure the coating is dry before exposing to the elements.

Wet Film Thickness ... 1 - 2 mil (25.4 - 50.8 microns)
 Dry Film Thickness 0.07 - 0.14 mil (1.8 - 3.6 microns)

Typical Coverage..... 800 - 1600 ft²/gal (19.7 - 39.4 m²/l)

Agitate before and during use.

BENEFITS:

- Zero VOC
- Excellent rust resistance during indoor humid storage conditions
- Protects up to 12 months
- Chrome free
- Barium free
- Environmentally safe
- Transparent
- Removes with KATS cleaners

APPLICATIONS:

The KATS 5550 can be applied to galvanized steel, galvanum, cold rolled steel and painted surfaces for indoor usage.

Industrial, Manufacturing, Agricultural, Truck, Auto, Mining, Railroad, Aerospace, RV, Boat

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
ASTM D-2247	Humidity Resistance Test 400 hrs @ 100°F (38°C)	Pass
ASTM D-1200	Viscosity Ford Cup #4 @ 72°F	6 - 12 sec
ASTM D-1475	Density	8.3 lb/gal (0.996 g/cm ³)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

A Division of The Whitmore Manufacturing Company

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
 An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • www.katscoatings.com

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.