

## 8077 REMOVER

KATS 8077 is a concentrated form of water based remover for KATS temporary coatings, which are typically used to protect vehicles, machines, etc. during transport.

Guidelines for use of KATS 8077:

The coating that is to be removed should remain wet during the removal process; therefore, do not work in direct sunlight during hot weather. The ideal temperature should be 60° - 80°F (16° - 27°C).

Apply KATS 8077 in a good ventilated area without excessive wind. Before using, review SDS and wear proper gear.

Apply KATS 8077 to the coated surface, diluted with 6 parts water by volume. Use a handheld compression sprayer or a KATS Decoater™ Applicator, available from KATS. Work from top to bottom.

The coating will become white or gray looking as it absorbs the remover and will slump from the surfaces. **DO NOT ALLOW THE COATING TO DRY DURING THE REMOVAL PROCESS.** In hot, dry, windy weather or where the coated item is large, it may be necessary to have several people working at the same time, or remove coating in sections.

Once the coating is removed, rinse off any residue of KATS 8077 thoroughly with clean water. This is particularly important around headlights and taillights to prevent any potential stress crack due to the residue.

Detailed instructions are available from KATS.

Shelf Life.....18 months from date of manufacture  
Storage Temperature.....40° - 80°F

### BENEFITS:

- 0.6 lb/gal (72 gm/liter) VOC
- Fast acting and user friendly
- Excellent remover for KATS temporary coatings
- Biodegradable
- Non-offensive citrus odor
- Contains no ammonia or phosphates

### APPLICATIONS:

- Removal of KATS temporary coatings
- Degreaser and cleaner

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
EPA 1110	Corrosiveness	Pass - Not considered corrosive
GM 9163P	6 Month Removal Test	Pass
GM 3.3.7	Compatibility Test	Pass
OECD 301D	Biodegradability	Pass
ASTM D-1475	Density	8.50 lb/gal (1.02 g/cm <sup>3</sup> )

*The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.*

### PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

A Division of Whitmore

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 1-800-699-6318

An ISO 9001 and ISO 14001 registered company • [www.katscoatings.com](http://www.katscoatings.com)

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.