

4010 RUST PROTECTIVE COATING - BLACK

KATS 4010 is a water based coating utilizing plant base polymer technology that both prevents rust and enhances appearance. The coating is black and semitransparent, with an attractive high gloss finish. It is suitable for use on both ferrous and nonferrous metals.

The surfaces to be protected should be clean and dry. Apply KATS 4010 in a good ventilated area without excessive wind. Before using, review MSDS and wear proper gear.

KATS 4010 can be applied using a water-compatible HVLP or conventional spray system. HVLP is recommended due to its transfer efficiency. Nordson Spray System can be utilized, if applicable.

Ambient/Surface temperature..... 45° - 100°F (7° - 38°C)
 Ideal Surface Temperature 60° - 80°F (16° - 27°C)
 Note: Insure the coating is dry before exposing to the elements. To minimize temperature/humidity variables, heated force drying is recommended to improve early water resistance.

Wet Film Thickness ... 2.5 mil (63.5 microns)
 Dry Film Thickness 0.5 mil (12.7 microns)

Typical Coverage..... 640 ft²/gal (15.7 m²/l)

BENEFITS:

- 0.75 lb/gal (90 grams per liter) VOC
- Water based
- Covers light rust
- Protects up to 12 months
- Quick drying
- No fire hazard
- HAPs-free
- Excellent adhesion to various surfaces.
- Environmentally safe

APPLICATIONS:

KATS 4010 is used primarily on oil country tubular goods (OCTG) and other types of metal tubing. It is also suitable for use on a wide variety of bare metal stock and finished goods.

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
ASTM D-2247	Humidity Chamber Test	Pass - 500 hours with less than 0.01% surface rust
ASTM B-117	Salt Spray Chamber	Pass - Less than 0.01% surface corrosion at 50 hours
ASTM D-2243	Freeze and Thaw Stability, Cycles Passed	5
ASTM D-1200	Viscosity Ford Cup #4 @ 72°F (22°C)	10 - 20 Seconds
ASTM D-1475	Density	8.5 lb/gal (1.02 g/cm ³)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
---------------------	--------------------	-------------------

A Division of Whitmore
 930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 1-800-699-6318
 An ISO 9001 and ISO 14001 registered company • www.katscoatings.com

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.