

## AVIATION WET WASH Zero-VOC Cleaner / Degreaser

Whitmore Aviation Wet Wash is based on green chemistry and is designed to conform to major aviation specifications. It does not contain any solvent, yet is highly effective in removing the various contaminants that aircraft are exposed to.

### Application instructions:

1. Read Safety Data Sheet and wear suitable protective gear.
2. Apply in well ventilated area. Best if applied to surfaces between 40°F and 80°F (4°C–27°C.) Use stream of tap water to adjust temperature if necessary.
3. Minimal agitation with a towel, pad or soft brush will be sufficient to promote emulsification of greasy / oily deposits.
4. Rinse thoroughly using water spray. Do not allow surfaces to become dry before rinsing.
5. Dry with clean towel.

Note: Thick grease buildup can be scraped off to improve cleaning time.

Shelf life: Eighteen months from date of manufacture.  
Ideal storage temperature: 40° - 80°F (4°C - 27°C)

### BENEFITS:

- Short dwell time and minimal agitation requirements save significant time and money
- Environmentally safe
- Zero VOC
- HAPs-free
- Biodegradable
- Contains no ammonia or phosphates
- No flash point

### APPLICATIONS:

- Exterior Surface Cleaning
  - ~ Wing-to-body fairing
  - ~ Landing gear & door
  - ~ Radome
  - ~ Wheel well & door
  - ~ Leading edge of flap & slat
  - ~ Engine compressor
- Interior airframe cleaning
- Ground support equipment

TEST METHOD	DESCRIPTION	TYPICAL CHARACTERISTIC
Boeing D6-17487	Exterior and General Cleaner	Approved/Conformed
AMS 1526C	Cleaner for Exterior surface (spec designed for small aircraft)	Approved/Conformed
Airbus AIMS 09-00-002	Exterior and General Cleaner	Approved/Conformed
	Aviation Grease Removability (Grease 22 and Grease 33MS)	Excellent
	Appearance/Odor	Clear, with slightly milky tint. Mild citrus odor
	pH	8 - 10
OECD 301D	Biodegradability	Readily biodegradable
ASTM D-2243	Freeze and Thaw Stability, cycles passed	5+
ASTM D-1475	Density	8.45 lb/gal (1.014 g/cm <sup>3</sup> )

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

### PACKAGING

5000 Gallon Bulk Tanker	260 Gallon Totes	55 Gallon Drums	5 Gallon Pails
----------------------------	---------------------	--------------------	-------------------

For warranty information, scan the QR code.  
You can also email us at [sales@whitmores.com](mailto:sales@whitmores.com)  
Or write to the Sales Department at the address below.



930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318  
An ISO 9001 and ISO 14001 registered company • [www.whitmores.com](http://www.whitmores.com)